Harmonia LED retrofit downlight

A modern looking downlight that has all the benefits of LED technology without incompatibility issues between MR16 lamps and existing tranformers.



Catalogue No. FLDL703MK16, FLDL903KMK16, FLDL704KMR16, FLDL904KMR16

Ideal for retrofitting MR16 halogen downlights in lift lobbies, cafés, hotels and shopping centres.

Features

- Smart integrated electronics ensure a smooth operation between lamp and transformer
- 7W (550lm) or 9W (710lm)
- Substantial energy saving when compared to a 35W or 50W MR16 halogen lamp
- Choice of 3,000K or 4,000K colour temperature
- 70mm or 90mm cut-out
- IP44
- Spring clips for ease of installation
- 3 year warranty
- Useful life of LEDs L70 @ 35,000 hours

FAMCO LIGHTING PTY LTD

T: (03) 9935 7300 **F**: (03) 9935 7301

E: info@famco.com.au

W: www.famco.com.au

All rights reserved. E&OE. Subject to change without notice to allow progress in design. This document and the information it contains is the property and copyright of Famco Lighting PTY LTD and must not be used, copied, transmitted or reproduced without our written permission.




Harmonia LED retrofit downlight

| Cat No. | FLDL703KMR16 | FLDL704KMR16 | FLDL903KMR16 | FLDL904KMR16 | |
|------------------------------|---------------|--------------|--------------|--------------|--|
| Supply voltage | 12V a.c. 50Hz | | | | |
| Input power | 7W | | 9W | | |
| Lumens output | 550lm | 590lm | 710lm | 770lm | |
| Colour temperature (Nominal) | 3000K | 4000K | 3000K | 4000K | |
| Colour Rendering Index (CRI) | 80+ | | | | |
| Beam angle | 85° | | 95° | | |
| Dimmable | No | | | | |
| IP rating | IP44 | | | | |
| Insulation Rating | CA90 | | IC | | |
| Ceiling cut-out size | Ø70mm | | Ø90mm | | |
| Depth into ceiling | 75mm | | | | |
| Fascia size | Ø93mm | | Ø110mm | | |

| Cat No. | Average lifespan | Installation condition | | | | |
|--------------|------------------|--|---------------|---|--|--|
| FLDL703KMR16 | | Rated average LED lamp life at | | / | | |
| FLDL704KMR16 | 35.000h | 25°C when installed with the default insulation clearances specified by | | | | |
| FLDL903KMR16 | 55,00011 | AS/NZS 3000:2007 | | / | | |
| FLDL904KMR16 | | | | | | |
| FLDL703KMR16 | 30.000h | Rated average LED lamp life at 25°C when installed with the thermal insulation abutting the fixture in | 00 0000000 | | | |
| FLDL704KMR16 | 30,00011 | accordance with the CA90 rating specified in AS/NZS 60598.2.2 | | | | |
| FLDL903KMR16 | 30.000h | Rated average LED lamp life at 25°C when installed with the thermal insulation abutting and covering the | 6 5 S | | | |
| FLDL904KMR16 | 30,00011 | fixture in accordance with the IC rating specified in AS/NZS 60598.2.2 | ABUTTED & | | | |

Note: This form of installation complies with the Wiring Rules AS/NZS 3000:2007 requirement for recessed downlights, clause 4.5.2.3.1 (i).

Installation








9W Harmonia LED







03/2017 FAM1317

FAMCO LIGHTING PTY LTD

T: (03) 9935 7300 F: (03) 9935 7301

E: info@famco.com.au

W: www.famco.com.au

All rights reserved. E&OE. Subject to change without notice to allow progress in design. This document and the information it contains is the property and copyright of Famco Lighting PTY LTD and must not be used, copied, transmitted or reproduced without our written permission.

LUMINAIRE DESIGNERS, MANUFACTURERS & SUPPLIERS

Dimensions 7W Harmonia LED







Ø90mm

Ø110mm



75mm