

LED Goldstar™ SURFACE MOUNT - D80/E16



A complete range of non-maintained Emergency luminaires for commercial applications.

FEATURES

- Electronics designed to lengthen the life of the battery, minimizing maintenance costs
- Environmentally friendly battery
- One high Brightness LED
- T-sense[™] temperature sensing technology for LIION
- Available in black or white finish
- Standalone or MasterMinder emergency monitored
- 5 year warranty
- Designed and Manufactured in Australia

APPLICATIONS

- Commercial offices
- Shopping centre
- Facilities
- Public Building applications

TECHNICAL INFORMATION

- Operating mode: Maintained
- Operating voltage: 240V a.c. +/- 6% 50Hz
- Power consumption: 2W
- Battery: Li-ion 6.4V, 3.0Ah
- IP rating: IP20
- Body construction: Polycarbonate (satellite head), steel (enclosure)
- Operating temperature: 10°C to 40°C
- Compliance: AS/NZS 2293 AS/NZS 60598





F9995/SMS/LI

| SPU | | |
|-----------------|-------------------------------------|-----------------------|
| Cat No | Description | Classification C0/C90 |
| F9995/SMS/LI | LED Goldstar Surface Mount White | D80/E16 |
| F9995/SMS/BL/LI | LED Goldstar Surface Mount Black | D80/E16 |


| MasterMinder | | |
|-----------------|--|-----------------------|
| Cat No | Description | Classification C0/C90 |
| FX9995/SMS/LI | MasterMinder LED Goldstar Surface Mount White | D80/E16 |
| FX9995/SMSBL/LI | MasterMinder LED Goldstar Surface Mount Black | D80/E16 |




LED Goldstar™ SURFACE MOUNT - D80/E16



DIMENSIONS





Spacing table: Maximum spacings between luminaires for 0.2 lux

| Mounting Height (m) | 2.4 | 2.7 | 3 | 3.3 | 3.6 | 4.0 |
|---------------------|------|------|------|------|------|------|
| A | 22.0 | 22.8 | 23.6 | 24.3 | 25.0 | 25.8 |
| В | 9.2 | 9.8 | 10.6 | 11.0 | 11.6 | 12.2 |

Spacing table: Maximum spacings between luminaires for 1 lux

| Mounting Height (m) | 2.4 | 2.7 | 3 | 3.3 | 3.6 | 4.0 |
|---------------------|------|------|------|------|------|-----|
| Α | 12.5 | 12.9 | 13.2 | 13.5 | 13.8 | 14 |
| В | 6.1 | 6.3 | 6.5 | 6.5 | 6.5 | 6.4 |

More info available at:

www.famco.com.au

