

Viking IP65

WEATHER PROOF BATTEN

The Famco Viking series of weatherproof, adverse environment luminaires for use in high humidity, dampness, dust and/or corrosive locations.

APPLICATIONS:

Wherever a dust & water resistant fitting is required.

- Carparks
- Building sites
- Food premises
- Chemical plants
- Hose down areas
- Railway areas
- Security areas
- Factories
- Public buildings
- Swimming pools

CONSTRUCTION

Polyester compression moulded body, glass reinforced (GRP)

Built in gasket

Prismatic lens with internal prism, smooth outer surface, injection moulded with sharp sealing ridges against gasket.

IP65 rated





Grommets supplied for cable entry at both ends.

Stainless steel toggle clips 316 grade


Polycarbonate lens

Supplied with electronic ballasts

Complies with AS/NZS 60598.1 and CISPR15:2006



FV98114/WD	1x14W	T5
FV98118/WD	1x18W	T8
FV98128/WD	1x28W	T5
FV98136/WD	1x36W	T8
FV98135/WD	1x35W	T5
FV98158/WD	1x58W	T8
FV98214	2x14W	T5
FV98218	2x18W	T8
FV98228	2x28W	T5
FV98236	2x36W	T8
FV98235	2x35W	T5
FV98258	2x58W	T8



FV98218 2X28W

Maximum Candela = 1197.89 Located At Horizontal Angle = 25, Vertical Angle = 5

- A. Vertical Plane Through Horizontal Angles (0 - 180)
- B. Vertical Plane Through Horizontal Angles (90 - 270)

Also available as emergency lighting version

Photometric data available at:

famco.com.au/product/viking-ip65

FAMCO LIGHTING PTY LTD

T: (03) 9935 7300 F: (03) 9935 7301 E: info@famco.com.au W: www.famco.com.au

© 2014 Famco Lighting Pty Ltd. All rights reserved. E&OE. Subject to change without notice, to allow progress in design. This document and the information it contains is the property and copyright of Famco Lighting Pty Ltd and must not be used, copied, transmitted or reproduced without our written permission.

