Weatherproof LED Exit Sign



FEATURES

- Electronics designed to lengthen the life of the battery, minimizing maintenance costs
- Environmentally friendly battery
- Two sizes: 24m and 32m viewing distance
- High resistance polycarbonate ABS clear cover
- Removable gear tray for ease of maintenance and installation
- Large terminal block for ease of connection
- Low cost maintenance
- T-sense[™] temperature sensing technology for LIION battery
- Designed and manufactured in Australia
- 5 year warranty


APPLICATIONS

Exterior: large and small spaces


TECHNICAL INFORMATION

- Operating mode: Maintained
- Supply voltage: 240V a.c. +/- 6% 50Hz
- Power consumption: 5.4W
- Battery: Li-ion 6.4V 1.5Ah
- IP rating: IP65
- IK rating: IK08
- Body construction: Polycarbonate
- Operating temperature: 10°C to 40°C
- Compliance: AS/NZS 2293 AS/NZS 60598

DIMENSIONS



24m Exit



32m Exit



24m



32m

Cat No	Description			
24m – SPU				
F9937LW/S/LI	WP LED Exit RM			
F9937LW/L/LI	WP LED Exit RML			
F9937LW/R/LI	WP LED Exit RMR			
24m – FMX				
FX9937LW/S/LI	FMX WP LED Exit RM			
FX9937LW/L/LI	FMX WP LED Exit RML			
FX9937LW/R/LI	FMX WP LED Exit RMR			
32m – SPU				
F9939LW/S/LI	WP LED Exit RM			
F9939LW/L/LI	WP LED Exit RML			
F9939LW/R/LI	WP LED Exit RMR			
32m – FMX				
FX9939LW/S/LI	FMX WP LED Exit RM			
FX9939LW/L/LI	FMX WP LED Exit RML			
FX9939LW/R/LI	FMX WP LED Exit RMR			


RM= Running Man straight, RML= Running Man left, RMR= Running Man right


Accessories	
F9937/WBKT	Wall bracket for 24m
F9937/CBKT	Ceiling bracket for 24m
F9937/SBKT	Side bracket for 24m

Weatherproof LED Exit Sign



Rear mounting bracket













Ceiling mounting bracket














Classification	Maximum spacing between luminaires 0.2 lux Mounting Height (Metres)				
Metres Classification	2.7	3	3.3	3.6	
E 2.5	5.8	5.8	6.0	5.8	
E 2	5.2	5.4	5.2	5.0	

Classification	Maximum spacing between luminaires 1 lux Mounting Height (Metres)				
Metres Classification	2.4	2.7	3.0	3.3	
E 2.5	N/A	N/A	N/A	N/A	
E 2	N/A	N/A	N/A	N/A	

More info available at: www.famco.com.au

© 2016 Famco Lighting Pty Ltd All rights reserved. E&OE. Subject to change without notice, to allow progress in design. This document and the information it contains is the property and copyright of Famco Lighting PP Ltd and must not be used, copied, transmitted or reproduced without our written permission.