# Eco Rapid LED Goldstar



## ECO RAPID

A general purpose non-maintained emergency luminaire with D40 classification

#### **FEATURES**

- Suitable for all emergency lighting applications
- Energy efficient: 1W energy consumption
- Easy-to-install spring clips
- Large trim included
- D40 classification
- 50,000 hour LED life
- Supplied complete with flex and plug
- T-sense<sup>™</sup> temperature sensing technology for the LIION battery
- Electronics designed to lengthen the life of the battery, minimising maintenance costs
- Environmentally friendly battery
- 3 year warranty
- Designed in Australia

#### **APPLICATIONS**

- Commercial office
- Educational facilities
- Hospitality

#### **TECHNICAL INFORMATION**

- Type: SPU
- Battery pack: Li-ion 6.4V 1500mAh
- Operating Voltage: 240V a.c. +/- 6% 50Hz
- Power Consumption: 1W
- Body Constructions: Polycarbonate
- Operating Temperature: 10° to 40°
- IP Rating: IP20
- Compliance: AS/NZS 2293 AS/NZS 60598



SPU	
Cat No	Description
F9975/LI	ECO RAPID LED GOLDSTAR D40 LITHIUM


Туре	Dish diameter	Hole cut-out		
No trim	85mmØ	70mmØ		
Large trim	140mmØ	70mm - 125mmØ		



#### SPACING TABLE

	Maximum spacing between luminaires (m)					
Height (m) Classification	2.7	3	3.3	3.6	4	
D40	18.0	18.6	19.1	19.6	20.1	

### **DIMENSIONS**





More info available at:

www.famco.com.au

