LED Goldstar Maximus





FEATURES

- Suitable for high ceilings and large areas.
- T-sense[™] temperature sensing technology for Li-ion battery.
- One high brightness LED.
- D100 Emergency classification.
- Standalone or MasterMinder emergency monitored.
- Several mounting options: surface, wall bracket, suspension rod or suspension wire.
- Available in grey and black finish.
- Compliant to AS/NZS 2293, AS/NZS 60590.



TECHNICAL INFORMATION

■ Nominal Input Voltage: 230 - 240 V a.c. 50 Hz

Battery: Li-ion 12.8 V, 1.5 AhPower Consumption: 5.2 W

■ Light Source: LED


■ Operating Temperature: 10° C to 40° C
■ Lighting Classification: C₀/C₉₀ D100
■ Light Source Life: 100,000 hrs
■ Body Construction: Polycarbonate


■ IP Rating: IP65 ■ IK Rating: IK07

■ Compliance: AS/NZS 2293, AS/NZS 60598

STANDALONE	
Cat. No.	Description
F9990/LI	LED GOLDSTAR MAXIMUS, D100, IP65, LITHIUM-GREY
F9990/BL/LI	LED GOLDSTAR MAXIMUS, D100, IP65, LITHIUM-GREY
MASTERMINDER	
FX9990/LI	LED GOLDSTAR MAXIMUS, D100, IP65, LITHIUM-GREY
FX9990/BL/LI	LED GOLDSTAR MAXIMUS, D100, IP65, LITHIUM-GREY

DIMENSIONS





ACCESSORY	
FROD/20/1200	SUSPENSION ROD AND CANOPY 1200MM LENGTH - GREY
FROD/20/3000	SUSPENSION ROD AND CANOPY 3000MM LENGTH - GREY
FROD/20/1200B	SUSPENSION ROD AND CANOPY 1200MM LENGTH - BLACK
FROD/20/3000B	SUSPENSION ROD AND CANOPY 3000MM LENGTH - BLACK
F9990/SUSP	SUSPENSION WIRE KIT - GREY
F9990/SUSPB	SUSPENSION WIRE KIT - BLACK
F9990/WBKT	WALL BRACKET - GREY
F9990/WBKTB	WALL BRACKET - BLACK