

LED Goldstar™ - D80/E16



A complete range of non-maintained Emergency luminaires for commercial applications.

FEATURES

- Suitable for all emergency lighting applications.
- Energy efficient: less than 1W energy consumption in stand by mode.
- 3 trim sizes available: Small, Medium and Large ring
- One high Brightness LED.
- T-sense™ temperature sensing technology for Li-ion battery.
- Easy to install spring clips.
- Available in Black or White finish.
- Standalone or MasterMinder emergency monitored.
- Manufactured in Australia.



APPLICATIONS


- Commercial offices
- Shopping centre
- Facilities
- Public Building applications

TECHNICAL INFORMATION

- Operating Mode: Maintained
- Nominal Input Voltage: 230-240 V a.c. 50 Hz
- Operating Voltage: 2 W
- Battery: Li-ion 6.4 V, 3.0 Ah
- Light Source Life (LSL): 100,000 hours
- IP Rating: IP20
- Operating temperature: 10°C to 40°C
- Body Construction: Polycarbonate
- Compliance: AS/NZS 2293, AS/NZS 60598

SPU		
Cat. No.	Description	Classification C0/C90
F9995/LI	LED GOLDSTAR FLEX AND PLUG - WHITE - LITHIUM	D80/E16
F9995/BL/LI	LED GOLDSTAR FLEX AND PLUG - BLACK - LITHIUM	D80/E16

MasterMinder		
Cat. No.	Description	Classification C0/C90
FX9995/LI	LED GOLDSTAR FLEX AND PLUG - WHITE - LITHIUM	D80/E16
FX9995/BL/LI	LED GOLDSTAR FLEX AND PLUG - BLACK - LITHIUM	D80/E16



SPACING TABLE

Maximum spacings between luminaires for 0.2 lux (Australia)

Mounting Height (m)	2.4	2.7	3.0	3.3	3.6	4.0
A	13.2	14.8	16.5	18.1	19.8	22.0
B	9.1	9.8	10.4	11.0	11.5	12.1

As per AS/NZS 2293:2018

Maximum spacings between luminaires for 1 lux (New Zealand)

Mounting Height (m)	2.4	2.7	3.0	3.3	3.6	4.0
A	12.5	12.9	13.3	13.6	13.8	14.1
B	6.1	6.4	6.5	6.6	6.6	6.4


As per AS/NZS 2293:2018

LED Goldstar™ - D80/E16





DIMENSIONS

Fascia



Type	Diameter (X*)
No trim	60 mm
Small Ring	80 mm
Medium Ring	120 mm
Large Ring	150 mm

SPU and MasterMinder Power Pack



More info available at:
www.famco.com.au